



WATERguard FILTRATION

INSTALLATION

1. Install in a location convenient for filter replacement.
2. For cold water use only.
3. After prolonged periods of non-use it is recommended that the system be flushed thoroughly. Let water run for 2-3 minutes before using.
4. The filter cartridge used with this system has a limited service life. Changes in taste, odor, color, and/or flow of the water being filtered indicate that the cartridge should be replaced.
5. In-line filter life depends upon the water volume used and the substances present in the in the water source. SHURflo recommends changing the filter every 6 to 12 months or when its capacity expires, whichever comes first.

MOUNTING

Mounting the Filter System:

- Select a location where filter system is to be mounted. **NOTE:** Allow 1-1/2 inches [38 mm] clearance below housing or 11 inches [279 mm] below filter head to enable filter cartridge changes. **CAUTION:** Filter head should be mounted securely to a solid stud or surface. The mounting bracket will support the weight of the filter and help prevent strain on the cold water line.
- Filter head should be mounted in vertical position, use the mounting bracket as a template to mark screw locations. Mount filter head in marked location using the screws provided in the hardware kit. **CAUTION:** Cold water supply to the filter should have a separate shut-off valve. If it does not, a separate shut-off should be installed.

Connecting the Tubing and fittings:

- Filter head is equipped with 3/8" quick connect fittings. Other fittings included are 1/2" NPT-M x 3/8" NPT-F (2), 3/8" Stem x 3/8" NPT-M (2) and 3/8" Stem x 1/4" Quick Connect (1).
- Use the appropriate fittings for your installation.
- Connect tubing and make sure all connections are secure. Turn on water and check for leaks.
- Allow water to run approximately 2 to 3 minutes to flush and saturate filter.
- You are now ready to enjoy "Great Tasting Healthy Clean Water"

Replacing the Cartridge:

- To remove old cartridge, twist cartridge counter clockwise until unlock arrows on cartridge and bracket line up. Pull down firmly to remove cartridge.
- To install new cartridge, line up arrows on cartridge and bracket. Push cartridge firmly into bracket and twist clockwise until locking arrows line up.



**Replacement Cartridge
Model #: RV-QDRF-A**

LIMITED WARRANTY

SHURflo warrants its WATERguard filters to be free from material and workmanship defects under normal use and service for a period of (1) one year from the date of purchase. In the absence of proof of purchase the warranty is (1) one year from the date of manufacture indicated on the label, not to exceed one year in any event. The limited warranty will not apply to WATERguards that were improperly installed, misapplied, or incompatible with components not manufactured by SHURflo. SHURflo will not warrant any WATERguard that is physically damaged, or altered outside the SHURflo factory. Warranty claims may be resolved by an authorized dealer service center, or by a SHURflo service center. All returns are to be shipped with charges pre-paid. Package all returns carefully. SHURflo will not be responsible for freight damage incurred during shipping to a service center. Warranty returns will be shipped on a freight allowed basis. SHURflo reserves the right to choose the method of transportation. SHURflo is not responsible nor will it reimburse for labor necessary to remove and reinstall a WATERguard, if found defective. This warranty is only a representation of the complete Marine Products Limited Warranty outlined by Service Bulletin #1050.

***DO NOT USE WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY WITHOUT ADEQUATE DISINFECTION BEFORE OR AFTER THE UNIT.**

SHURflo reserves the right to update specifications, prices, or make substitutions.



SHURflo, LLC Headquarters

5900 Katella Avenue
Cypress, California 90630
Phone (562) 795-5200 • Toll Free (800) 854-3218
Fax (562) 795-7564

911-762 Rev D
© 2008 SHURflo, LLC All Rights Reserved

SHURflo, LLC East

52748 Park Six Court
Elkhart, Indiana 46514-5427
Phone (562) 795-5200 • Toll Free (800) 854-3218
Fax (574) 264-2169

SHURflo Europe, Middle East, Africa

Pentair Water Belgium bvba,
Industriepark Wolfstee, Toekomstlaan 30
B-2200 Herentals, Belgium
Phone +32-14-283500 • Fax +32-14-283505

ECO #: 16135

Page 1 of 1